



## FLOW

surface


**EN** Square aluminium luminaire housing, flat design (luminaire housing 35mm); surface powder coated; suitable for wall or ceiling mounting, luminaire housing set 11mm away from wall or ceiling; convenient quick mounting system without tools; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; completely homogeneous illumination; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**FR** Corps de luminaire carré en aluminium, forme plate (corps de luminaire 35mm) ; surface thermolaquée ; convient au montage mur ou plafond, corps de luminaire 11mm décalé du mur ou du plafond ; système de montage rapide, convivial et sans outil ; distribution de lumière directe par LGP-Body (Light Guiding Prism) ; lumière couplée latéralement guidée vers le bas par gravure laser ; guidage lumière au moyen de matériau réflecteur hautement réfléchissant ; éclairage parfaitement homogène ; luminance identique pour toutes les variantes de taille ; LED économes en énergie à restitution de couleur élevée ; luminaire avec 2 ouvertures câblage et borne enfichable pour câblage passant

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 80, 3 SDCM  
 up to 146 lm/W  
 L90 @ 50000h  
 non DIM, DALI-2  
 opal, IP40

### Types



### Colours



### Light distribution



DiiA® standards  
 251, 252, 253



easy mounting by  
 click-mechanism



insect protection  
 (IP40)

**Order options**

<b>COLOUR TEMPERATURE</b>	••
3000K	5
4000K	6

<b>CONTROL</b>	◆
non DIM	1
DALI-2	3


<b>MATERIAL COLOUR</b>	■
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours ● p. 992	X

<b>LIGHT OPTIC COVER</b>	
opal	


**Options on request**

<b>MOUNTING</b>	
1500 mm cable suspension	


<b>COLOUR RENDERING INDEX</b>	
CRI ≥ 90	

**FLOW 320 surface****DIRECT**

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15.2 W	3000 K	2000 lm	0 7 3 - 0 1 3 1 ◆◆◆ O
	4000 K	2120 lm	

**FLOW 450 surface****DIRECT**

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
23.9 W	3000 K	3250 lm	0 7 3 - 0 1 4 1 ◆◆◆ O
	4000 K	3440 lm	

**FLOW 600 surface****DIRECT**

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
44 W	3000 K	6060 lm	0 7 3 - 0 1 5 1 ◆◆◆ O
	4000 K	6420 lm	

**Accessories**

TYPE	ORDER CODE
dismounting tool	0 7 3 - 0 1 0 0 0 0